

Neusilin® UFL2

Technical Data Sheet

www.neusilin.com

Neusilin® - The Specialty Excipient

A synthetic magnesium aluminometasilicate (MAS) with exceptional excipient properties for improving actives delivery and quality of pharmaceutical preparations. Although chemically the same as traditional crystalline MAS, Neusilin® is both structurally and functionally a very different product that serves a multitude of purposes when compared to other silicates.

Key Features

- Improves powder flowability
- Anti-caking agent for hygroscopic powders
- Oil adsorption of poorly water soluble actives
- Stabilization of deliquescent drugs
- Improves tablet and powder capsule quality

General Properties

Chemical formula	$Al_2O_3 \cdot MgO \cdot 1.7SiO_2 \cdot xH_2O$
General name	Magnesium Aluminometasilicate
Appearance	White powder
Form	Amorphous
Solubility	Practically insoluble in water and ethanol
Composition (%) on dried basis	Al_2O_3 29.1 - 35.5 MgO 11.4 - 14.0 SiO_2 29.2 - 35.6
Degree of whiteness	> 95
Loss on drying 110°C/7hrs (%)	< 7
Bulk density	Loose (g/ml) 0.06 - 0.11
	Tapped (g/ml) 0.10 - 0.17
True specific gravity	2.2
Specific surface area (m ² /g)	300
Average particle size (µm)	3.1
Angle of repose (°)	45
Oil adsorbing capacity (ml/g)	2.7 - 3.4
Water adsorbing capacity (ml/g)	2.4 - 3.1
Acid consuming capacity (ml/g)	≥ 210
Ph 4% slurry	6.0 - 8.0

Typical Application and Quantity Required

Application / function	Quantity (%)
Excipient / diluent	30 - 90
Tablet - binder, disintegration aid, increase hardness	1 - 10
Increase flowability	0.5 - 5
Anticaking agent	0.5 - 5
For suspensions	1 - 5
Stabilization of deliquescent drugs	5 - 15
Solidification of liquid pharmaceutical preparations	30 - 50
Solid dispersion, SMEDDS	20 - 50

Pharmacopoeia & Regulatory


Neusilin® meets all requirements of the current USP/NF and JPC. US DMF Type IV filed in 1998.

Handling & Storage

Packaging: 5 kg double-lined Kraft bags

Storage: Store at room temperature and avoid high humidity.

Shelf life: 3 years from the date of manufacture stored in recommended conditions.



Neusilin® UFL2 (×20,000)



Fuji Chemical Industries USA, Inc.

3 Terri Lane, Unit 12, Burlington, NJ 08016

Tel: 609-386-3030 Fax: 609-386-3033

www.fujichemicalUSA.com contact@fujichemicalUSA.com

Information found is presented in good faith with no guarantee or obligation as to accuracy and no assumption of liability. The information herein does not imply a performance warranty. Purchasers should decide the suitability of the product with respect to their desired application and purpose. Standard specifications and product grades, although current at the time of publication, are subject to change without notice.